

3-Eier Newsletter

by hire
LICHT-TECHNIK

grandMA



grandMA 2 Light

- 6x DMX out
- Real-time control for with MA NPU up to 256 DMX universes
- 4,096 HTP-/LTP-parameters built-in
- 2 internal TFT wide mode touchscreens (15.4" WXGA);
- 2 external TFT screens can be connected (UXGA, can be touchscreens);
- 1 internal command screen – multi-touch
- 15 motorized executor faders
- Built-in UPS; 2 Ethercon connectors;
- 5 USB 2.0 port;
- 2 motorized A/B fader 100mm

LED-PAR



Expolight TourLED 42 CM WP

- DMX, schwarz, 16°, IP67, Doppelbügel
- 14x 3W Tri-Color Highpower LEDs
- Stromverbr: 73W;
- 100-240 VAC, 50/60 Hz; 3, 4, 5, 10-DMX-Kanäle;
- Schuko Adapter
- Außenliegende DMX 3-pol Kabel in / out

150 Stk. verfügbar

Wireless Solution



WDMX WirelessSolution

- Signalübertragung über 500m
- Receiver, Wireless Solution R-512
- Hochleistungsantenne 2dBi
- Hochleistungsantenne 5dBi
- Transmitter Wireless Solution
- Hochleistungsantenne



Moonlight

The EventWare® Company

Preisinformation und Buchung unter:

0800-EventWare